

HYGISEAT Automatic self-cleaning toilet



WC suspendu automatique design HYGISEAT

HYGISEAT Automatic self-cleaning toilet wall hung design version

Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax: 2172,00 €

Sales price: 2172,00 €

Sales price without tax: 1810,00 €

[Ask a question about this product](#)

Description

HYGISEAT Automatic self-cleaning toilet wall hung design version

AUTOMATIC WC with free touch cleaning cycle triggering, disinfection, seat drying and water flush after each use.

Seat rotation cycle: water supply pressure mixed with disinfecting Germibloc, seat drying.

Cycle time: 12 seconds



[SUP1500](#)
[HYGISEA](#)
[I movie](#)

Total safety

- 12 volts power supply by external transformer 230/12V.
- Immediate device stop in case of irregular motion.

- Manual flush button in case of power failure.
- CE norm compliant. 3 years limited warranty.



OPTIONS:

Ref. SUP 1065: double detection option (passing the hand or user departure)

Seat cleaning triggering and flush by hand approach **OR AUTOMATIC cycle triggering after the user's departure**

Ref. SUP 1080: blue spreading product option in the bowl , foaming, scale inhibitor and cleaning at the user arrival. Included SUP 1065.

Ref. SUP 1070: SaniAir odour extraction system option. Without filter, efficient odour extraction system directly to the source in the bowl to evacuate in the waste-water pipes. Allows to reduce ambient humidity and to fight against the aerosol flush effect spreading bacterias. Insuring the toilet ventilation and preserving the heat usually losted in the ceiling aspiration system. Includes SUP 1065. Not available with option SUP1080.

Ref. SUP 1095: colour option ([according to the RAL palette](#))

Bright or matt finish



Matt black



Bright pink

Installation on [support-frame and hidden tank GEBERIT/HYGISEAT](#)

DIMENSIONS Dim. H 820 x L 410 x P 535 mm



Hygiseat system advantages:

- Eliminates contacts with dirt seat.
- Eliminates contacts with flush control.

- Reduce smells and insure publicwashrooms sanitary conditions.
- Reduce maintenance time and costs.
- Ergonomical shape retention, without gripping points and easy maintenance; specially designed for projections to the seat insuring a perfect hygiene, without bacterias spreadings.
- Waterproof sensor cell (100 immerged hours at 65° C), IP 67, immune to vibration and electrical perturbations, insensitive to luminous interference.
- Robust for sites exposed to vandalism, intensive use and easy maintenance.

[Downloads](#)

[TECHNICAL DATA](#)