

RONDEO TRIO washbasin frame for wall mounted electronic faucets

Reference: **RES-KE3-123**

Description

RONDEO TRIO washbasin iron support frame, with integrated faucets for cold or pre-mixed water, and electronic soap dispenser and hand dryer.

Allows for robust and simple installation.

Vandal-proof spout mounting on metal frame.

Touch-free, ensures optimal hygiene and user comfort.

Drastic reduction in water and soap consumption.

Minimizes water splashes on the floor and around the washbasin.

Adjustable drain, washbasin and faucet heights.

Provides a complete electronic soap and water solution, as well as all installation components (excluding washbasin).

Features

Adjustable frame height from 1140 to 1340 mm.

Galvanised swivel feet, adjustable 0-200 mm.

Washbasin fixing centre distance 60 - 360 mm.

40/40 mm C-profile frame. Blue epoxy paint.

Cover to protect openings from moisture and dirt, to be cut to suit wall thickness.

Self-adjusting infrared sensor or settings adjustable by RES-31 remote control detection range, flow duration, periodic flushing, temporary stop, reset...).

Hand dryer power and volume level adjustable by control dial. Hepa filter.

CE. 3 year warranty.

Delivered with

RONDEO automatic soap dispenser 150 mm spout - RONDEO electronic faucet 170 mm spout - RONDEO automatic hand dryer 220 mm spout - Drain elbow $\varnothing$ 50 mm - $\varnothing$ 44/32 mm gasket - 2 M10 threaded rods for washbasin and bolt covers - Floor and wall fixing accessories.

Reference

RONDEO TRIO washbasin support frame

• **RES-KE3-123** soap, water, air - on mains



Options

- RES-31 Remote control
- RES-790 6 L soap tank to supply from 1 to 6 dispensers
- RES-294 IP 68 transformer to supply from 1 to 4 faucets and soap dispensers
- RES-296 Junction box to supply from 1 to 10 faucets and soap dispensers
- Limited water flow of 1.3, 1.9 or 3 LPM
- Extended water spout L version 220 mm or XL version 295 mm and soap spout L version 177 mm
- Finishes: matte black, PVD matte gold or PVD copper
- AISI 316 brushed stainless steel finish
- Mixer tap

RONDEO TRIO washbasin frame for wall mounted electronic faucets

Reference: RES-KE3-123

RONDEO Electronic Faucet	
Installation	Recessed and wall mounted with support frame.
Power supply	12V transformer (for soap and water with power splitter).
Water pressure	0.5 - 8 bars.
Water supply	Cold or pre-mixed water.
Limited water flow	6 LPM – 3LPM / 1,9LPM / 1,3 LPM option.
Maximum temperature	Max 70°C.
Security stop	After 90 seconds with no interruptions (adjustable with remote control).
Hygienic rinse	24H after last use

RONDEO Soap Dispenser	
Installation	Recessed and wall mounted with support frame.
Power supply	12V transformer (for soap and water with power splitter).
Soap	1 L tank. Peristaltic pump for all types of liquid soap, detergent or hydro-alcoholic gel. 2L, 6L or generic tank option.
Standard discharge	1.2 -1.6 cc (adjustable with remote control).
Soap refill	Prime the soap with button located on pump or by remote control.

RONDEO Hand Dryer	
Installation	Recessed and wall mounted with support frame.
Rated power	Adjustable from 800 to 1600 W (accessible button on motor bloc).
Power supply	220-240V 50-60Hz, 1,3-1,6 KW. 6.1-6.7 A amperage.
Thermal motor protection	Auto Resetting Thermostat turns unit off at 95 °C.
Thermal protection resistance	Auto Resetting Thermostat turns unit off at 85°C. Thermal fuse cuts unit off at 142 °C.
Stand-by power	0.3 - 0.4 W.
Security stop	After 60 seconds with no interruptions.
Detection range	170 mm ± 20, self-adjusting
IP rating	IP34

