

TECHNICAL SHEET

## Collective wash through with back splash INTER-5-D





Collective wash through made with back splash in stainless steel quality AISI 304, satin finish. Side thickness 1,5 mm / basin 1 mm.

Innovative concept guaranteeing a perfect hygiene since the wash trough is completely welded on the inside: no splits nor joints.

Interior corners within the wash through length > 90° for an easy clean.

Flat bottom allowing a 15L. bucket to be placed.

80 mm space for taps with H 292 mm back splash.

Basin depth 142 mm. Perforated central drainage grid 1 1/2".

Quick and efficient assembly, with 4 fixation points.

Standard compliant EN14296 on the resistance to sanitary appliances loads.

Dim. W620 to 3000 x D474 x H434 x mm.

**Options:** tap holes ø 22 or ø 35 mm, custom made (max 3 m).

## References:

| INTER-5-60-D  | 1 place / 600 mm   |
|---------------|--------------------|
| INTER-5-100-D | 2 places / 1000 mm |
| INTER-5-120-D | 2 places / 1200 mm |
| INTER-5-140-D | 2 places / 1400 mm |
| INTER-5-150-D | 3 places / 1500 mm |
| INTER-5-180-D | 3 places / 1800 mm |
| INTER-5-200-D | 4 places / 2000 mm |
| INTER-5-210-D | 4 places / 2100 mm |
| INTER-5-240-D | 4 places / 2400 mm |
| INTER-5-280-D | 5 places / 2800 mm |
| INTER-5-300-D | 5 places / 3000 mm |

The stainless steel by their held on chrome, which provides a remarkable resistance to corrosion and wear and tear (the surface film « liability»). Chromed stainless steel type 441 doesn't make any exception, and is used with success in important applications such as sinks, washing machine drum, exhaust systems...

