TECHNICAL SHEET

Collective wash through in stainless steel INTER-7 for wall mounted taps



Collective wash through made in stainless steel quality AISI 441, satin finish. Side thickness 1,5 mm / basin 0.8 mm.

Innovative concept guaranteeing a perfect hygiene since the wash trough is completely welded on the inside: no splits nor joints.


Interior corners within the wash through length $> 90^{\circ}$ for an easy clean.

Flat bottom allowing a 15L. bucket to be placed.

Basin depth 142 mm. Perforated central drainage grid 1 1/2".

Quick and efficient assembly, with 4 fixation points.

Standard compliant EN14296 on the resistance to sanitary appliances loads.



Options: pair of stainless steel feet, custom made (max 3 m), back splash.

References:

INTER-7-60	1 place / 600 mm
INTER-7-100	2 places / 1000 mm
INTER-7-120	2 places / 1200 mm
INTER-7-140	2 places / 1400 mm
INTER-7-150	3 places / 1500 mm
INTER-7-180	3 places / 1800 mm
INTER-7-200	4 places / 2000 mm
INTER-7-210	4 places / 2100 mm
INTER-7-240	4 places / 2400 mm
INTER-7-280	5 places / 2800 mm
INTER-7-300	5 places / 3000 mm

The stainless steel by their held on chrome, which provides a remarkable resistance to corrosion and wear and tear (the surface film « liability»). Chromed stainless steel type 441 doesn't make any exception, and is used with success in important applications such as sinks, washing machine drum, exhaust systems...

